



DuraSOL™ Medium Display Film 12 mil

■ satin 3608

PRODUCT DESCRIPTION

3608 DuraSOL™ Medium is a 12 mil semi-rigid PVC display film with a “low glare” satin finish and an instant dry, scratch resistant coating. The durable construction features tear resistant PVC intended to be used un laminated to create a durable tradeshow or rollup panel engineered to withstand repeated rolling in portable display units without cupping, warping or scratching. DuraSOL™ 3508 and 3608 are compatible with solvent and UVC printers.

Physical Properties

Caliper	12 mil
Basis Weight	430 g/m ²
Gloss (60°)	10
Opacity	> 99%
*All values listed are target values	

Advantages

- Tear Resistant PVC Base
- Semi-Rigid PVC Base
- Water & Scratch Resistant
- Low Glare Satin Finish
- Durable Without Lamination

Applications

- Scratch Resistant Pop-Ups with no Overlamine needed
- Trade Shows, Banks, Retail & Airport Signage

List of printers



Printer	Ink
Epson® GS 6000	Eco-Solvent I
Hewlett Packard® DJ 8000s, 9000s, 10000s	Low-Solvent
Hewlett Packard H35000, H45000	788 UV pigment inks
Mimaki® JV3, JV33, JV 5	ES, SS2, SS2-1, HS
Mimaki® UVJ / UJV 160	UV Curable
Mutoh® ValueJet	Eco-Solvent
Roland® VP, SP, XC, XJ, SJ / AJ	ECO-SOL MAX / Eco-Xtreme
Océ Arizona 250 GT, 200GT	UV Inks
FujiFilm Acuity HD 2504	UV Inks
Vutek PV, QS, DS Series	UV Ink

*For further information please refer to our website www.sihlinc.com

How to Buy

For additional Sihl Digital Imaging product information, please call 1-800-366-7393 or visit our website www.sihlinc.com where you can also find an authorized Sihl reseller near you.