



simply the better solution

Sihl Inc.  
800.366.7393  
www.sihlinc.com



## Value Line Media

## Sihl Quick Reference Guide

Certified for  
HP Latex Inks

## PAPER

3672	<b>Performance SL Paper</b> Roll Length: 165'   Width: 30", 54", 63" Roll Length: 656'   Width: 63" • Satin finish, Outdoor Durable, Fold without Cracking	<b>190gsm/ 8mil</b>	<b>SLU</b>   3" Core   6" Core
3673	<b>Performance SL Paper</b> Roll Length: 200'   Width: 54", 63" • Satin finish, Outdoor Durable, Fold without cracking	<b>130 gsm/ 6mil</b>	<b>SLUH</b>   3" Core
3211	<b>Blockout Paper</b> Roll Length: 150'   Width: 54", 60" • Satin finish, Printable 2 sides, 100% opacity, PVC free	<b>300gsm/ 10.5mil</b>	<b>LU</b>   3" Core

## CANVAS

3213	<b>Economy Canvas</b> Roll Length: 60'   Width: 24", 36", 44", 60" • Matte finish, 1:1 Weave Structure, 65/35% Poly/Cotton Blend Canvas	<b>365gsm/ 17mil</b>	<b>ALU</b>   3" Core
3222	<b>Economy Solvent Canvas</b> Roll Length: 75'   Width: 36", 54", 60" • Reliable Poly/Cotton Blend, No Surface or Edge Cracking, 1:1 weave	<b>315gsm/ 15mil</b>	<b>SLU</b>   3" Core

## POINT OF SALE MEDIA - Banner

3216	<b>Economy Roll Up</b> Roll Length: 100'   Width: 36", 50" • Non curling Grayback, Smooth Low Glare Finish	<b>335gsm/ 10mil</b>	<b>SLU</b>   3" Core
3396	<b>"Big Dog" Roll-Up Banner</b> Roll Length: 100'   Width: 36", 50" • 100% Polyester, Lay Flat, Tear Resistant, Grayback	<b>280gsm/ 8mil</b>	<b>SLU</b>   3" Core

## POINT OF SALE MEDIA - Floor Graphics

3234	<b>AlumaMax Adhesive Floor &amp; Wall Graphics</b> 470gsm/ 17.7mil Roll Length: 32.8'   Width: 37.8", 54" • Conforms to rigid and textured surfaces • Slip Proof ( Conforms to ANSI/NFSI B101.3 )	<b>300</b>   3" Core
3235	<b>Speedy Vinyl No-Slip Floor Graphic</b> 495gsm/ 10mil Roll Length: 82'   Width: 54" • Scrim / Nylon reinforced • Slip Proof ( Conforms to ANSI/NFSI B101.3 / UL 410 )	<b>300</b>   3" Core
3236	<b>Turtle Vinyl Floor Graphic</b> 430gsm/ 8.5mil Roll Length: 98'   Width: 54" • Use with smooth surfaces (Ex. smooth tile or linoleum) • Slip resistant (Conforms to ANSI 137.1, 326.3 and B101.3 standards) • Flame Retardent - Certified as ASTM-E84 Class A	<b>300</b>   3" Core

## POINT OF SALE MEDIA - Window Perf

3214	<b>60/40 Window Perf</b> 12.5mil (6.5mil vinyl/6mil liner) Roll Length: 100'   Width: 54", 60" Roll Length: 164'   Width: 54", 60" • Removable clear acrylic adhesive • 1.5 mm hole	<b>300</b>   3" Core
3215	<b>80/20 Window Perf</b> 12mil (6mil vinyl/6mil liner) Roll Length: 100'   Width: 54" Roll Length: 164'   Width: 54", 60" • Removable clear acrylic adhesive • 1.5 mm hole	<b>30</b>   3" Core
3218	<b>50/50 Window Perf</b> 12.5mil (6.5mil vinyl/6mil liner) Roll Length: 100', 164'   Width: 54" • Removable clear acrylic adhesive • 1.6 mm hole	<b>300</b>   3" Core
3226	<b>70/30 UV Window Perf</b> 15.5mil (7mil vinyl/8.5mil liner) Roll Length: 164'   Width: 54", 60" • Double liner to avoid clogging holes • 1.5 mm hole	<b>300</b>   3" Core
3231	<b>70/30 Non-Adhesive Window Perf PET</b> 10mil (8mil vinyl/2mil liner) Roll Length: 82'   Width: 54" • Designed for interior glass installations • 1.6 mm hole, Use with 3232	<b>30</b>   3" Core

For more information, please visit [Sihlinc.com](http://Sihlinc.com) where you can find spec sheets, instruction guides, and even certifications for all of our great products. These will be available under our support and downloads tab and can be easily downloaded. You can also use the following QR codes for a direct link to each of these pages.

Value Line Spec Sheets



ICC Profiles



Instruction Guides

